

# ANSUL® F-CLASS MODEL M6L PORTABLE FIRE EXTINGUISHER

Data/Specifications



## FEATURES

- Meets the requirements of EN3 and PED
- Simple operation and maintenance
- Rechargeable
- Easy-to-read pressure gauge
- Extended discharge range up to 5 m (16 ft)
- Swirl effect multi-purpose nozzle
- Steel cylinder finished in red, high-quality, polyester powder coating
- Corrosion resistant internal protective coating
- Suitable for use on live electrical equipment up to 1000VAC

## APPLICATIONS

The ANSUL® F-Class Model M6L liquid agent fire extinguisher is specifically designed for use on fires that involve combustible vegetable or animal fats in commercial cooking equipment. Typical appliances include fryers; griddles; range tops; upright, natural charcoal, or chain-type broilers; electric, lava rock, mesquite or gas-radiant char-broilers; and woks.

Newer, more efficient cooking appliances, plus the use of non-saturated cooking oils, require a fire extinguishing agent which will not only smother a fire but provide a cooling effect.

The extinguisher is ideally suitable for use in restaurants, hospitals, nursing homes, hotels, schools, airports, and other similar facilities.

It is used as a backup to an automatic fire suppression system. The energy source to the cooking equipment shall be shut off by the automatic system to help suppress the fire and permit the cooking media to cool below its auto-ignition temperature.

## DESCRIPTION

The ANSUL F-Class Model M6L is attractive and easy to use or maintain.

The low pH fire extinguishing agent used in the extinguisher is a specially-formulated aqueous solution. It has been developed to provide rapid flame extinguishment and securement of hot fuels such as cooking shortenings.

## CODES

Pressure Equipment Directive (PED) – CE marked product  
European standard for portable extinguisher – EN3



008086

## SPECIFICATIONS

Model	M6L
EN Rating	13A, 75F
Capacity	6 Liters (1.6 Gallon)
Height	560 mm (22 in.)
Width	230 mm (9 in.)
Range	3-5 m (9.8-16.4 ft)
Discharge Time	33 seconds
Temperature Range	0 °C – 60 °C (32 °F – 140 °F)

## ORDERING INFORMATION

Description	Part No.
ANSUL F-Class Model M6L Liquid Agent Fire Extinguisher	
German Language	011 915
Czech Language	011 948
English Language	011 949
Spanish Language	011 950
French Language	011 951
Neufrol M (Wet Chemical Agent) 6 Liters (1.6 Gallon)	300 415

ANSUL is a trademark of Ansul Incorporated or its affiliates.



Ansul Incorporated  
Marinette, WI 54143-2542

715-735-7411  
www.ansul.com

Copyright ©2008 Ansul Incorporated  
Form No. F-2008103